

# Product Data Sheet Neo Armor Ultra ™ 6-235-Q11

MEDIUM WEIGHT POLYURETHANE COATED, MACHINE KNITTED LEVEL F GLOVE WITH AN INTEGRAL ELASTICATED WRIST





Gauge	13 gg
Liner	HPPE

Liner Colours Salt & Pepper

Dipping Coverage Palm Coated

**Coating** PU

Coating Colour Black, Grey

#### **Features**

- Ultra-fine polyurethane coating offers excellent tacky grip in dry and also good in lighter oil conditions for safe and secure handling and extended glove life.
- Low shredding polyurethane coating and continues filament yarn together make much lower tendency to create dust, suitable for clean environment with limited dust.
- Seamless knitted liner with ultra-fine polyurethane coating provides excellent tactile feel, snug fitting and superior dexterity.
- Innovation blend of special high performance fibers, offers excellent mechanical performance
- Product is in compliance with reach directives and azo free dyestuff, content of DMF maintained to the lowest level to make perfect clean glove.

#### **Applicable Industries**

### **Glove Type**

#### Hazard

Automotive

Cut Resistance

Cut

- Packaging
- Assembly Operation
- Aerospace Industry
- Automotive Paint Line
- Metal Fabrication
- Electronics



#### **Certifications**

CE Category II Certificate EN ISO 21420:2020 EN 388:2016 (4X42F) ANSI Cut Level 6









#### **Dimension**

		M/8	L/9	XL/10	XXL/11	XXXL/12
А	Total Glove Length (mm) (±8)	225	235	245	255	265
В	Wrist Length (mm) (±5)	70	70	75	80	85
С	Wrist width (mm) (±5)	80	80	85	85	90
D	Palm width (mm) (±5)	100	105	110	115	118

## **Packaging**

Description

12 Pairs with a Sleeve Pack is packed in a Poly Bag with a User Instruction Sheet (UIS)